

M-UNIVERSAL

M-DIAGNOSTIC

M-SCIENCE



PDF





Easier access to the centrifuge chamber made of stainless steel.

FEATURES

modern design

low noise level

maintenance-free induction motor

modern software system

large graphic LCD - blanking the screen after a period of inactivity

2 screen modes (simplified and normal)

10 menu languages (PL, EN, ES, IT, PT, DE, RU, FR, SE, CZ)

visual and sound alerts of different notifications

100 user programs

10 acceleration/deceleration curves

speed or RCF adjustment

manual centrifugal radius adjustment (with automatic RCF correction)

time calculation from start key pressing or from reaching preselected speed

ascending or descending time counting

continuous operation mode - HOLD

SHORT time operation mode

changing of parameters during centrifuging

automatic rotor recognition

automatic lid opening

stainless steel rotor chamber

selected functions blocking, password protection

effective ventilation system

SAFETY












unbalance sensor










lid locking during rotor running

start blocking at opened lid

emergency lid lock release

product conforming with the EN-61010-1 and EN-61010-2-020, EN-61010-2-101 standards

	S-LINE				M-LINE				
									
	MPW-54	MPW-55	MPW-56	MPW-150R	M-BASIC	M-UNIVERSAL	M-DIAGNOSTIC	M-SCIENCE	MPW-260
	120 ml	48 ml	120 ml	90 ml	120 ml / PRP	500 ml	500 ml	100 ml	500 ml
RCF max.	1 137, 3 122 x g	15 279 x g	3 341 x g	21 382 x g	2 469 x g	24 270 x g	4 830 x g	24 270 x g	24 270 x g
RPM max.	3 500, 5 800	14 500	6 000	15 000	4 000	18 000	6 000	18 000	18 000
	-	-	-	-20°C ÷ +40°C	-	-	-	-	-
Number of rotors (angle swing-out)	3/0	3/1	4/0	7/1	1	19/4	8/5	8/1	19/3
Rotor auto-recognition	-	-	-	•	-	•	•	•	•
Language	EN	EN	EN	PL, EN, ES, IT, PT, DE, RU, SE, FR, CZ	EN	PL, EN, ES, IT, PT, DE, RU, SE, FR, CZ	PL, EN, ES, IT, PT, DE, RU, SE, FR, CZ	PL, EN, ES, IT, PT, DE, RU, SE, FR, CZ	PL, EN, ES, IT, PT, DE, RU, SE, FR, CZ
Cover tightening	-	-	-	-	-	-	-	-	-
User programs	-	9	-	100	5	100	100	100	100

	M-LINE		L-LINE				XL-LINE	
								
	MPW-260R	MPW-260RH	MPW-351e	MPW-352	MPW-352R	MPW-352RH	MPW-380	MPW-380R
	500 ml	500 ml	800 ml	1 000 ml	1 000 ml	1 000 ml	3 000 ml	3 000 ml
RCF max.	24 270 x g	24 270 x g	3 509 x g	29 703 x g	30 065 x g	30 065 x g	31 876 x g	31 876 x g
RPM max.	18 000	18 000	4 500	18 000	18 000	18 000	18 000	18 000
	-20°C ÷ +40°C	-20°C ÷ +55°C	-	-	-20°C ÷ +40°C	-20°C ÷ +55°C	-	-20°C ÷ +40°C
Number of rotors (angle swing-out)	19/3	19/3	4/3	27/7	27/7	27/7	13/4	13/4
Rotor auto-recognition	•	•	-	•	•	•	•	•
Language	PL, EN, ES, IT, PT, DE, RU, SE, FR, CZ	PL, EN, ES, IT, PT, DE, RU, SE, FR, CZ	EN	PL, EN, ES, IT, PT, DE, RU, SE, FR, CZ	PL, EN, ES, IT, PT, DE, RU, SE, FR, CZ	PL, EN, ES, IT, PT, DE, RU, SE, FR, CZ	PL, EN, ES, IT, PT, DE, RU, SE, FR, CZ	PL, EN, ES, IT, PT, DE, RU, SE, FR, CZ
Cover tightening	-	-	-	•	•	•	•	•
User programs	100	100	-	100	100	100	100	100



46 Boremlowska Street
04-347 Warsaw Poland

MPW MED. INSTRUMENTS
www.mpw.pl

E-mail: mpw@mpw.pl
Phone.: +48 22 610 56 21
Fax: +48 22 610 55 36

